

Chemical Safety Data Sheet MSDS / SDS

2-Butanol

Revision Date:2024-11-16 Revision Number:1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product name : 2-Butanol
CBnumber : CB0751661
CAS : 78-92-2
EINECS Number : 201-158-5
Synonyms : 2-butanol, butan-2-ol

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : For R&D use only. Not for medicinal, household or other use.
Uses advised against : none

Company Identification

Company : Chemicalbook
Address : Building 1, Huihuang International, Shangdi 10th Street, Haidian District, Beijing
Telephone : 400-158-6606

SECTION 2: Hazards identification

GHS Label elements, including precautionary statements

Symbol(GHS)



Signal word

Warning

Precautionary statements

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash hands thoroughly after handling.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continuerinsing.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P337+P313 IF eye irritation persists: Get medical advice/attention.
P370+P378 In case of fire: Use ... for extinction.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
P501 Dispose of contents/container to.....

Hazard statements

H226 Flammable liquid and vapour
H319 Causes serious eye irritation
H335 May cause respiratory irritation
H336 May cause drowsiness or dizziness
H361 Suspected of damaging fertility or the unborn child

SECTION 3: Composition/information on ingredients

Substance

Product name	: 2-Butanol
Synonyms	: 2-butanol, butan-2-ol
CAS	: 78-92-2
EC number	: 201-158-5
MF	: C ₄ H ₁₀ O
MW	: 74.12

SECTION 4: First aid measures

Description of first aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Call in physician.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂) Foam Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

Special hazards arising from the substance or mixture

Carbon oxides Combustible.

Vapors are heavier than air and may spread along floors. Risk of dust explosion.

Forms explosive mixtures with air at elevated temperatures.

Development of hazardous combustion gases or vapours possible in the event of fire.


Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.

Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

NFPA 704



■ HEALTH 1 Exposure would cause irritation with only minor residual injury (e.g. [acetone](#), sodium bromate, potassium chloride)

Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature

■ FIRE 3 conditions. Liquids having a flash point below 22.8 °C (73 °F) and having a boiling point at or above 37.8 °C (100 °F) or having a flash point between 22.8 and 37.8 °C (73 and 100 °F). (e.g. gasoline, [acetone](#))

■ REACT 0 Normally stable, even under fire exposure conditions, and is not reactive with water (e.g. helium, [N₂](#))

□ SPEC.

□ HAZ.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition.

Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

Environmental precautions

Do not let product enter drains. Risk of explosion.

Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent material (e.g. Chemisorb?). Dispose of properly. Clean up affected area.

Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Change contaminated clothing. Wash hands after working with substance. For precautions see section 2.2.

Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

control parameter

Hazard composition and occupational exposure limits

Does not contain substances with occupational exposure limits.

Exposure controls

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0,4 mm Break through time: 480 min

Material tested: Camatril? (KCL 730 / Aldrich Z677442, Size M)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact Material: Chloroprene

Minimum layer thickness: 0,65 mm Break through time: 120 min Material tested: KCL 720 Camapren?

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

Recommended Filter type: Filter A (acc. to DIN 3181) for vapours of organic compounds

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

Exposure limits

TLV-TWA 450 mg/m³ (150 ppm) (NIOSH), 305 mg/m³ (100 ppm) (ACGIH); IDLH 10,000 ppm.

SECTION 9: Physical and chemical properties

Information on basic physicochemical properties

Appearance	colorless liquid
Odour	alcohol-like
Odour Threshold	43 ppm
pH	No data available
Melting point/freezing point	Melting point/range: -115 °C - lit.
Initial boiling point and boiling range	98 °C - lit.
Flash point	27 °C - closed cup

Evaporation rate	No data available
Flammability (solid, gas)	No data available
Upper/lower flammability or explosive limits	Upper explosion limit: 9,8 %(V) Lower explosion limit: 1,7 %(V)
Vapour pressure	15,3 hPa at 20 °C
Vapour density	2.6 (vs air)
Relative density	No data available
Water solubility	ca.18 g/l at 20 °C - soluble
Partition coefficient: n-octanol/water	log Pow: 0,65 at 25 °C - Bioaccumulation is not expected.
Autoignition temperature	No data available
Decomposition temperature	No data available
Viscosity	Viscosity, kinematic: No data available Viscosity, dynamic: 4,703 mPa.s at 15 °C
Explosive properties	No data available
Oxidizing properties	No data available
Henry's Law Constant	1.19 (static headspace-GC, Merk and Riederer, 1997)

Other safety information

Surface tension 23 mN/m at 20 °C

SECTION 10: Stability and reactivity

Reactivity

Vapor/air-mixtures are explosive at intense warming.

Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

Possibility of hazardous reactions

Exothermic reaction with: Alkali metals

Alkaline earth metals Strong oxidizing agents

strong reducing agents Aluminum

acid halides chromium(VI) oxide

Conditions to avoid

Heating.

Incompatible materials

Aluminum, rubber, various plastics, Strong oxidizing agents

Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - male and female - 2.193 mg/kg

(OECD Test Guideline 423)

LC50 Inhalation - Rat - 4 h - 48,5 mg/l Remarks: (RTECS)

LD50 Dermal - Rat - male and female - > 2.000 mg/kg (OECD Test Guideline 402)

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation - 4 h (OECD Test Guideline 404)

Serious eye damage/eye irritation

Eyes - Rabbit Result: Eye irritation

(OECD Test Guideline 405)

Respiratory or skin sensitization

Germ cell mutagenicity

Test Type: Ames test

Test system: S. typhimurium

Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 471

Result: negative

Test Type: Chromosome aberration test in vitro Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 473

Result: negative

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Toxicity

LD50 orally in Rabbit: 6480 mg/kg LD50 dermal Rat > 2000 mg/kg

SECTION 12: Ecological information

Toxicity

Toxicity to fish

static test LC50 - Leuciscus idus melanotus - 3.520 mg/l - 48 h Remarks: (ECHA)

Toxicity to daphnia and other aquatic invertebrates

static test EC50 - Daphnia magna (Water flea) - 2.300 mg/l - 24 h Remarks: (ECHA)

Persistence and degradability

Biodegradability aerobic - Exposure time 5 d

Result: 86 % - Readily biodegradable. Remarks: (ECHA)

Bioaccumulative potential

No data available

Mobility in soil

No data available

Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Other adverse effects

No interference with wastewater treatment plants are to be expected when used properly. Discharge into the environment must be avoided.

SECTION 13: Disposal considerations

Waste treatment methods

Incompatibilities

Butyl alcohols may form explosive mixture with air. In all cases they are incompatible with oxidizers; contact may cause fires or explosions. Keep away from alkaline materials, strong bases, strong acids, oxoacids, epoxides. Attacks some plastics, rubber and coatings. n-Butanol is incompatible with strong acids; halogens, caustics, alkali metals; aliphatic amines; isocyanates.

Product

See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

Waste Disposal

Incineration, or bury absorbed waste in an approved land fill.

SECTION 14: Transport information

UN number

ADR/RID: 1120 IMDG: 1120

UN proper shipping name

ADR/RID: BUTANOLS IMDG: BUTANOLS IATA: Butanols

Transport hazard class(es)

ADR/RID: 3 IMDG: 3 IATA: 3

Packaging group

ADR/RID: III IMDG: III IATA: III

Environmental hazards

ADR/RID: no IMDG Marine pollutant: no IATA: no

Special precautions for user

No data available

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations on the Safety Management of Hazardous Chemicals

China Catalog of Hazardous chemicals 2015:Listed. website: <https://www.mem.gov.cn/>

Measures for Environmental Management of New Chemical Substances

Chinese Chemical Inventory of Existing Chemical Substances (China IECSC):Listed. website: <https://www.mee.gov.cn/>

EC Inventory:Listed.

European Inventory of Existing Commercial Chemical Substances (EINECS):Listed. website: <https://echa.europa.eu/>

Korea Existing Chemicals List (KECL):Listed. website: <http://ncis.nier.go.kr>

New Zealand Inventory of Chemicals (NZIoC):Listed. website: <https://www.epa.govt.nz/>

Philippines Inventory of Chemicals and Chemical Substances (PICCS):Listed. website: <https://emb.gov.ph/>

Vietnam National Chemical Inventory:Listed. website: <https://chemicaldata.gov.vn/>

United States Toxic Substances Control Act (TSCA) Inventory:Listed. website: <https://www.epa.gov/>

SECTION 16: Other information

Abbreviations and acronyms

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

CAS: Chemical Abstracts Service

EC50: Effective Concentration 50%

IATA: International Air Transportation Association

IMDG: International Maritime Dangerous Goods

LC50: Lethal Concentration 50%

LD50: Lethal Dose 50%

RID: Regulation concerning the International Carriage of Dangerous Goods by Rail

STEL: Short term exposure limit

TWA: Time Weighted Average

References

[1] CAMEO Chemicals, website: <http://cameochemicals.noaa.gov/search/simple>

[2] ChemIDplus, website: <http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp>

【3】 ECHA - European Chemicals Agency, website: <https://echa.europa.eu/>

【4】 eChemPortal - The Global Portal to Information on Chemical Substances by OECD, website:

http://www.echemportal.org/echemportal/index?pageID=0&request_locale=en

【5】 ERG - Emergency Response Guidebook by U.S. Department of Transportation, website: <http://www.phmsa.dot.gov/hazmat/library/erg>

【6】 Germany GESTIS-database on hazard substance, website: <http://www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index-2.jsp>

【7】 HSDB - Hazardous Substances Data Bank, website: <https://toxnet.nlm.nih.gov/newtoxnet/hsdb.htm>

【8】 IARC - International Agency for Research on Cancer, website: <http://www.iarc.fr/>

【9】 IPCS - The International Chemical Safety Cards (ICSC), website: <http://www.ilo.org/dyn/icsc/showcard.home>

【10】 Sigma-Aldrich, website: <https://www.sigmaaldrich.com/>

Other Information

Check for peroxides prior to distillation; eliminate if found.

Disclaimer:

The information in this MSDS is only applicable to the specified product, unless otherwise specified, it is not applicable to the mixture of this product and other substances. This MSDS only provides information on the safety of the product for those who have received the appropriate professional training for the user of the product. Users of this MSDS must make independent judgments on the applicability of this SDS. The authors of this MSDS will not be held responsible for any harm caused by the use of this MSDS.