

Chemical Safety Data Sheet MSDS / SDS

Methyl acrylate

Revision Date:2025-01-25 Revision Number:1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product name : Methyl acrylate
CBnumber : CB8669773
CAS : 96-33-3
EINECS Number : 202-500-6
Synonyms : methyl acrylate,Methyl ester

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : For R&D use only. Not for medicinal, household or other use.
Uses advised against : none

Company Identification

Company : Chemicalbook
Address : Building 1, Huihuang International, Shangdi 10th Street, Haidian District, Beijing
Telephone : 400-158-6606

SECTION 2: Hazards identification

GHS Label elements, including precautionary statements

Symbol(GHS)



Signal word

Danger

Precautionary statements

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash hands thoroughly after handling.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continuerinsing.

P307+P311 IF exposed: call a POISON CENTER or doctor/physician.

P311 Call a POISON CENTER or doctor/physician.

P370+P378 In case of fire: Use ... for extinction.

P405 Store locked up.

Hazard statements

H225 Highly Flammable liquid and vapour

H302 Harmful if swallowed

H312 Harmful in contact with skin

H314 Causes severe skin burns and eye damage

H315 Causes skin irritation

H317 May cause an allergic skin reaction

H319 Causes serious eye irritation

H331 Toxic if inhaled

H332 Harmful if inhaled

H335 May cause respiratory irritation

H341 Suspected of causing genetic defects

H370 Causes damage to organs

H372 Causes damage to organs through prolonged or repeated exposure

H373 May cause damage to organs through prolonged or repeated exposure

H401 Toxic to aquatic life

H412 Harmful to aquatic life with long lasting effects

SECTION 3: Composition/information on ingredients

Substance

Product name	: Methyl acrylate
Synonyms	: methyl acrylate,Methyl ester
CAS	: 96-33-3
EC number	: 202-500-6
MF	: C ₄ H ₆ O ₂
MW	: 86.09

SECTION 4: First aid measures

Description of first aid measures

General advice

First aiders need to protect themselves. Show this material safety data sheet to the doctor

If inhaled

After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Consult a physician.

In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂) Foam Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

Special hazards arising from the substance or mixture

Carbon oxides Combustible.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapours possible in the event of fire. Forms explosive mixtures with air at ambient temperatures.

Advice for firefighters


Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

NFPA 704





HEALTH	3	Short exposure could cause serious temporary or moderate residual injury (e.g. liquid hydrogen , sulfuric acid , calcium hypochlorite , hexafluorosilicic acid)
FIRE	3	Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions . Liquids having a flash point below 22.8 °C (73 °F) and having a boiling point at or above 37.8 °C (100 °F) or having a flash point between 22.8 and 37.8 °C (73 and 100 °F). (e.g. gasoline, acetone)
REACT	2	Undergoes violent chemical change at elevated temperatures and pressures, reacts violently with water, or may form explosive mixtures with water (e.g. white phosphorus, potassium , sodium)
SPEC.		
HAZ.		

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition.

Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

Environmental precautions

Do not let product enter drains. Risk of explosion.

Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g.

Chemisorb?). Dispose of properly. Clean up affected area.

Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition. Keep locked up or in an area accessible only to qualified or authorized persons.

Storage stability

Recommended storage temperature 2 - 8 °C

Light sensitive.

Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

control parameter

Hazard composition and occupational exposure limits

Does not contain substances with occupational exposure limits.

Exposure controls

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: butyl-rubber

Minimum layer thickness: 0,7 mm Break through time: 480 min Material tested: Butoject? (KCL 898)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact Material: Nitrile rubber

Minimum layer thickness: 0,4 mm Break through time: 30 min

Material tested: Camatril? (KCL 730 / Aldrich Z677442, Size M)

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

Recommended Filter type: Filter A (acc. to DIN 3181) for vapours of organic compounds

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

Exposure limits

TLV-TWA 10 ppm ($\sim 35 \text{ mg/m}^3$) (ACGIH and MSHA), TLV-TWA skin 10 ppm ($\sim 35 \text{ mg/m}^3$) (OSHA); IDLH 1000 ppm (NIOSH).

SECTION 9: Physical and chemical properties

Information on basic physicochemical properties

Appearance	colorless clear, liquid
Odour	pungent
Odour Threshold	0.0035ppm
pH	at 20 °C neutral
Melting point/freezing point	Melting point/range: -75 °C - lit.
Initial boiling point and boiling range	80 °C - lit.
Flash point	-2,8 °C - closed cup
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Upper/lower flammability or explosive limits	Upper explosion limit: 25 %(V) Lower explosion limit: 2,8 %(V)
Vapour pressure	90 hPa at 20,2 °C 150 hPa at 30,8 °C
Vapour density	2,97 - (Air = 1.0)
Relative density	0,95 at 20 °C
Water solubility	ca.60 g/l at 20 °C
Partition coefficient: n-octanol/water	log Pow: 0,74 at 25 °C - Bioaccumulation is not expected.
Autoignition temperature	468 °C at 1.013,25 hPa
Decomposition temperature	No data available
Viscosity	Viscosity, kinematic: 10 mm ² /s at 23 °C Viscosity, dynamic: 0,472 mPa.s at 25 °C
Explosive properties	No data available
Oxidizing properties	No data available
Henry's Law Constant	($\times 10^{-4} \text{ atm}\cdot\text{m}^3/\text{mol}$): 1.3 at 20 °C (approximate - calculated from water solubility and vapor pressure)

Other safety information

Surface tension 24,2 mN/m at 20 °C

Relative vapor density

2,97 - (Air = 1.0)

SECTION 10: Stability and reactivity

Reactivity

Vapors may form explosive mixture with air.

Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

Possibility of hazardous reactions

Risk of explosion with:

Peroxides

Strong oxidizing agents Strong acids

strong alkalis Activated charcoal

Conditions to avoid

Heat. May polymerize on exposure to light. Warming.

Incompatible materials

No data available

Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

No data available

LD50 Oral - Rat - male - 768 mg/kg (OECD Test Guideline 401)

Symptoms: Irritations of mucous membranes in the mouth, pharynx, oesophagus and gastrointestinal tract.

Acute toxicity estimate Inhalation - 4 h - 3 mg/l (Calculation method)

Symptoms: mucosal irritations, Cough, Shortness of breath, Possible damages:, damage of respiratory tractLC50 Inhalation - Rat - male and female - 4 h - < 10,8 mg/l

(OECD Test Guideline 403)

Acute toxicity estimate Dermal - 1.251 mg/kg (Calculation method)

LD50 Dermal - Rabbit - 1.250 mg/kg Remarks: (ECHA)

Skin corrosion/irritation

Skin - Rabbit

Result: irritating - 4 h (OECD Test Guideline 404)

Serious eye damage/eye irritation

Eyes - Rabbit Result: Eye irritation Remarks: (IUCLID)

Respiratory or skin sensitization

(OECD Test Guideline 429)

Germ cell mutagenicity

Test Type: Ames test

Result: Not mutagenic in Ames Test. Remarks: (IUCLID)

Test Type: Micronucleus test Species: Mouse

Cell type: Bone marrow

Application Route: inhalation (vapor)

Result: negative Remarks: (ECHA)

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

Inhalation - May cause respiratory irritation.

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Toxicity

LD50 orally in rats: 0.3 g/kg (Smyth, Carpenter)

SECTION 12: Ecological information

Toxicity

Toxicity to fish

flow-through test LC50 - Oncorhynchus mykiss (rainbow trout) - 3,4 mg/l - 96 h

(OECD Test Guideline 203)

flow-through test LC50 - Cyprinodon variegatus (sheepshead minnow) - 1,1 mg/l - 96 h

(OECD Test Guideline 203)

Toxicity to daphnia and other aquatic invertebrates

flow-through test EC50 - Daphnia magna (Water flea) - 2,6 mg/l - 48 h

(OECD Test Guideline 202)

Toxicity to algae

static test ErC50 - Pseudokirchneriella subcapitata (green algae) - 3,55 mg/l - 96 h

(OECD Test Guideline 201)

Toxicity to bacteria

static test EC10 - activated sludge - > 100 mg/l - 72 h Remarks: (ECHA)

Persistence and degradability

Biodegradability aerobic - Exposure time 28 d

Result: 90 - 100 % - Readily biodegradable. (OECD Test Guideline 310)

Bioaccumulative potential

No data available

Mobility in soil

No data available

Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Toxics Screening Level

The current initial threshold screening level (ITSL) for methyl acrylate is 70 µg/m³ based on an annual averaging time.

Other adverse effects

No data available

SECTION 13: Disposal considerations

Waste treatment methods

Product

See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

Incompatibilities

Forms explosive mixture in air. Incompatible with nitrates, oxidizers, such as peroxides, strong alkalis. Polymerizes easily from heat, light, peroxides; usually contains an inhibitor, such as hydroquinone.

Waste Disposal

Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

SECTION 14: Transport information

UN number

ADR/RID: 1919 IMDG: 1919 IATA: 1919

UN proper shipping name

ADR/RID: METHYL ACRYLATE, STABILIZED IMDG: METHYL ACRYLATE, STABILIZED

IATA: Methyl acrylate, stabilized

Transport hazard class(es)

ADR/RID: 3 IMDG: 3 IATA: 3

Packaging group

ADR/RID: II IMDG: II IATA: II

Environmental hazards

ADR/RID: no IMDG Marine pollutant: no IATA: no

Special precautions for user

No data available

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations on the Safety Management of Hazardous Chemicals

China Catalog of Hazardous chemicals 2015: Listed. website: <https://www.mem.gov.cn/>

Measures for Environmental Management of New Chemical Substances

Vietnam National Chemical Inventory: Listed. website: <https://chemicaldata.gov.vn/>

United States Toxic Substances Control Act (TSCA) Inventory: Listed. website: <https://www.epa.gov/>

Korea Existing Chemicals List (KECL): Listed. website: <http://ncis.nier.go.kr>

European Inventory of Existing Commercial Chemical Substances (EINECS): Listed. website: <https://echa.europa.eu/>

EC Inventory: Listed.

Chinese Chemical Inventory of Existing Chemical Substances (China IECSC): Listed. website: <https://www.mee.gov.cn/>

New Zealand Inventory of Chemicals (NZIoC): Listed. website: <https://www.epa.govt.nz/>

Philippines Inventory of Chemicals and Chemical Substances (PICCS): Listed. website: <https://emb.gov.ph/>

SECTION 16: Other information

Abbreviations and acronyms

CAS: Chemical Abstracts Service

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

RID: Regulation concerning the International Carriage of Dangerous Goods by Rail

IMDG: International Maritime Dangerous Goods

IATA: International Air Transportation Association

TWA: Time Weighted Average

STEL: Short term exposure limit

LC50: Lethal Concentration 50%

LD50: Lethal Dose 50%

EC50: Effective Concentration 50%

References

【1】 CAMEO Chemicals, website: <http://cameochemicals.noaa.gov/search/simple>

【2】 ChemIDplus, website: <http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp>

【3】 ECHA - European Chemicals Agency, website: <https://echa.europa.eu/>

【4】 eChemPortal - The Global Portal to Information on Chemical Substances by OECD, website:

http://www.echemportal.org/echemportal/index?pageID=0&request_locale=en

【5】 ERG - Emergency Response Guidebook by U.S. Department of Transportation, website: <http://www.phmsa.dot.gov/hazmat/library/erg>

【6】 Germany GESTIS-database on hazard substance, website: <http://www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index-2.jsp>

- 【7】 HSDB - Hazardous Substances Data Bank, website: <https://toxnet.nlm.nih.gov/newtoxnet/hsdb.htm>
- 【8】 IARC - International Agency for Research on Cancer, website: <http://www.iarc.fr/>
- 【9】 IPCS - The International Chemical Safety Cards (ICSC), website: <http://www.ilo.org/dyn/icsc/showcard.home>
- 【10】 Sigma-Aldrich, website: <https://www.sigmaaldrich.com/>

Other Information

An added stabilizer or inhibitor can influence the toxicological properties of this substance, consult an expert. The odour warning when the exposure limit value is exceeded is insufficient. Do NOT take working clothes home.

Disclaimer:

The information in this MSDS is only applicable to the specified product, unless otherwise specified, it is not applicable to the mixture of this product and other substances. This MSDS only provides information on the safety of the product for those who have received the appropriate professional training for the user of the product. Users of this MSDS must make independent judgments on the applicability of this SDS. The authors of this MSDS will not be held responsible for any harm caused by the use of this MSDS.