# Chemical Safety Data Sheet MSDS / SDS

# PROPYLENE

Revision Date:2025-02-01 Revision Number:1

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **Product identifier**

Product name	: PROPYLENE
CBnumber	: CB3750579
CAS	: 115-07-1
EINECS Number	: 204-062-1
Synonyms	: Propylene,propene
Relevant identified uses of	the substance or mixture and uses advised against
Relevant identified uses	: For R&D use only. Not for medicinal, household or other use.
Uses advised against	: none
Company Identification	
Company	: Chemicalbook
Address	: Building 1, Huihuang International, Shangdi 10th Street, Haidian District, Beijing
Telephone	: 400-158-6606

# SECTION 2: Hazards identification

#### Classification of the substance or mixture

Gases under pressure: Compressed gas

Flammable gases, Category 1A, Flammable gas

#### Label elements

#### Pictogram(s)

Signal word

Danger

#### Hazard statement(s)

H220 Extremely flammable gas

H280 Contains gas under pressure; may explode if heated

#### Precautionary statement(s)

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381 Eliminate all ignition sources if safe to do so.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

1

#### Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

#### Response

P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381 In case of leakage, eliminate all ignition sources.

#### Storage

P410+P403 Protect from sunlight. Store in a well-ventilated place.

P403 Store in a well-ventilated place.

#### Disposal

none

#### Other hazards

no data available

# SECTION 3: Composition/information on ingredients

#### Substance

: PROPYLENE
: Propylene,propene
: 115-07-1
: 204-062-1
: C3H6
: 42.08

### SECTION 4: First aid measures

#### Description of first aid measures

#### If inhaled

Fresh air, rest. Artificial respiration may be needed. Refer for medical attention.

#### Following skin contact

ON FROSTBITE: rinse with plenty of water, do NOT remove clothes. Refer for medical attention .

#### Following eye contact

First rinse with plenty of water for several minutes (remove contact lenses if easily possible), then refer for medical attention.

#### **Following ingestion**

Rinse mouth with water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Call a doctor or Poison Control Center immediately.

#### Most important symptoms and effects, both acute and delayed

Moderate concentration in air causes dizziness, drowsiness, and unconsciousness. Contact with liquefied propylene will cause ``freezing burn." (USCG, 1999)

#### Indication of any immediate medical attention and special treatment needed

If splashes of liquid propylene cause freezing of the skin, never rinse the affected area with hot or tepid water. If liquid propylene contacts the eyes flush eyes with water for 15 minutes.

# **SECTION 5: Firefighting measures**

#### **Extinguishing media**

Do not extinguish fire unless flow can be stopped. If possible use foam, carbon dioxide, or dry chemical to extinguish fire. If none of these compounds are available use water in flooding quantities as a fog, being sure to cool all affected containers. Apply water from as far a distance as possible, and do not use solid streams of water since they may be ineffective. Keep material out of water sources and sewers and build dikes as necessary to contain flow. Wear self contained breathing apparatus, boots, protective gloves and goggles and be sure to wash away any material which may have contacted the body with copious amounts of water or soap and water. Do not handle damaged packages without protective equipment. If fire becomes uncontrollable or a container is exposed to direct flame, evacuate for a radius of 2500 feet. If material leaking (and is not on fire), downwind evacuation must be considered.

#### **Specific Hazards Arising from the Chemical**

Behavior in Fire: Containers may explode. Vapor is heavier than air and may travel considerable distance to a source of ignition and flash back. (USCG, 1999)

#### Advice for firefighters

Shut off supply; if not possible and no risk to surroundings, let the fire burn itself out. In other cases extinguish with powder, carbon dioxide. In case of fire: keep cylinder cool by spraying with water. NO direct contact with water. Combat fire from a sheltered position.

#### **NFPA 704**



# SECTION 6: Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

Evacuate danger area! Consult an expert! Ventilation. Remove all ignition sources. NEVER direct water jet on liquid. Personal protection: chemical protection suit including self-contained breathing apparatus.

#### **Environmental precautions**

Evacuate danger area! Consult an expert! Ventilation. Remove all ignition sources. NEVER direct water jet on liquid. Personal protection: chemical protection suit including self-contained breathing apparatus.

#### Methods and materials for containment and cleaning up

Spills in Water: Contain contaminated water if possible by using natural barriers or oil spill control booms to limit spreading. A universal gelling agent may be applied to solidify trapped mass and to increase effectiveness of the booms. If solubilized, application of activated carbon at 10% spill amount over region occupied by 10 mg/L or greater concentrations is recommended. Spills on Land: Contain if possible by forming mechanical and/or chemical barriers to prevent spreading. Apply universal gelling agent to immobilize spill or use fly ash or cement powder to absorb the liquid. Leaking containers should be removed to an isolated well-ventilated area and if possible, the contents transferred to other suitable containers. Safety goggles, impervious clothing and positive pressure self-contained breathing apparatus should be worn. Plastic or neoprene-coated canvas gloves should be worn when liquid propylene is handled.

## SECTION 7: Handling and storage

#### Precautions for safe handling

NO open flames, NO sparks and NO smoking. Closed system, ventilation, explosion-proof electrical equipment and lighting. Prevent build-up of electrostatic charges (e.g., by grounding) if in liquid state. Handling in a well ventilated place. Wear suitable protective clothing. Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Use non-sparking tools. Prevent fire caused by electrostatic discharge steam.

#### Conditions for safe storage, including any incompatibilities

Fireproof. Cool.Protect cylinder against physical damage and from excessive temperature rise by storing away from sources of heat. No part of a cylinder should be subjected to a temperature above 52 deg C. Store cylinders in an upright position and firmly secured. Segregate full and empty cylinders. Isolate from oxygen and other oxidizers. Avoid exposure to areas where salt or other corrosive chemicals are present. Ground and bond all lines and equipment used with propylene. Do not use near sparking motors or other non explosion proof equipment.

### SECTION 8: Exposure controls/personal protection

#### **Control parameters**

**Occupational Exposure limit values** 

TLV: 500 ppm as TWA; A4 (not classifiable as a human carcinogen)

#### Biological limit values

no data available

#### Exposure controls

Ensure adequate ventilation. Handle in accordance with good industrial hygiene and safety practice. Set up emergency exits and the riskelimination area.

#### Individual protection measures

Eye/face protection		
Wear safety goggles or face shield.		
Skin protection		
Cold-insulating gloves.		
Respiratory protection		
Use ventilation.		
Thermal hazards		
no data available		

# SECTION 9: Physical and chemical properties

#### Information on basic physicochemical properties

Physical state	Colorless gas
Colour	Colorless gas
Odour	Aromatic
Melting point/freezing point	-185°C(lit.)
Boiling point or initial boiling point and	-47.7°C(lit.)
boiling range	
Flammability	Extremely flammable.
Lower and upper explosion	11.1%
limit/flammability limit	
Flash point	-108°C
Auto-ignition temperature	851° F (USCG, 1999)
Decomposition temperature	no data available
pH	no data available
Kinematic viscosity	83.4 micropoises at 16.7 deg C
Solubility	44.6 mL/100 mL (NTP, 1992)
Partition coefficient n-octanol/water	log Kow = 1.77
Vapour pressure	15.4 atm ( 37.7 °C)
Density and/or relative density	1.49
Relative vapour density	1.48 (vs air)
Particle characteristics	no data available

# SECTION 10: Stability and reactivity

#### Reactivity

Reacts violently with oxidants. This generates fire and explosion hazard.

#### **Chemical stability**

no data available

#### Possibility of hazardous reactions

DANGEROUS FIRE RISK. The gas is heavier than air and may travel along the ground; distant ignition possible. The gas is heavier than air and may accumulate in lowered spaces causing a deficiency of oxygen. As a result of flow, agitation, etc., electrostatic charges can be generated. During an experiment to produce lactic acid by oxidizing PROPYLENE with nitrogen peroxide, a violent explosion occurred. These mixtures (olefins and nitrogen peroxide) form extremely unstable nitrosates or nitrosites (Comp. Rend. 116:756 1893). Contact of very cold liquid propylene with water may result in vigorous or violent boiling of the product and extremely rapid vaporization due to the large temperature differences involved. If the water is hot, there is the possibility that a liquid "superheat" explosion may occur. Pressures may build to dangerous levels if liquid propylene contacts water in a closed container.

#### Conditions to avoid

no data available

#### Incompatible materials

Propylene reacts vigorously with oxidizing materials and with nitrogen dioxide (NO2), dinitrogen tetraoxide (N2O4), and dinitrogen oxide (N2O). Furthermore, liquid propylene will explode on contact with water at 42-75 deg C.

#### Hazardous decomposition products

Combustion products of propylene ... include carbon dioxide and carbon monoxide.

# SECTION 11: Toxicological information

#### Acute toxicity

- Oral: no data available
- Inhalation: LC50 Rat inhalation 570,000 ppm/15 min Conditions of bioassay not specified in source examined
- Dermal: no data available

#### Skin corrosion/irritation

no data available

#### Serious eye damage/irritation

no data available

#### Respiratory or skin sensitization

no data available

#### Germ cell mutagenicity

no data available

#### Carcinogenicity

Evaluation: There is inadequate evidence in humans for the carcinogenicity of propylene. There is inadequate evidence in experimental animals for the carcinogenicity of propylene. Overall evaluation: Propylene is not classifiable as to its carcinogenicity to humans (Group 3).

#### **Reproductive toxicity**

#### STOT-single exposure

Rapid evaporation of the liquid may cause frostbite. The substance may cause effects on the central nervous system. Exposure could cause lowering of consciousness. See Notes.

#### STOT-repeated exposure

no data available

#### Aspiration hazard

On loss of containment this substance can cause suffocation by lowering the oxygen content of the air in confined areas.

# SECTION 12: Ecological information

#### Toxicity

Toxicity to fish: no data available Toxicity to daphnia and other aquatic invertebrates: no data available Toxicity to algae: no data available Toxicity to microorganisms: no data available

#### Persistence and degradability

In water bodies, propylene is readily degraded by microorganisms and is therefore not expected to bioaccumulate or bioconcentrate in organisms and food chains.

#### **Bioaccumulative potential**

An estimated BCF of 5 was calculated for propylene(SRC), using a log Kow of 1.77(1) and a regression-derived equation(2). According to a classification scheme(3), this BCF suggests the potential for bioconcentration in aquatic organisms is low(SRC).

#### Mobility in soil

The Koc of propylene is estimated as 220(SRC), using a log Kow of 1.77(1) and a regression-derived equation(2). According to a classification scheme(3), this estimated Koc value suggests that propylene is expected to have moderate mobility in soil.

#### **Toxics Screening Level**

The initial threshold screening level (ITSL) for propylene (CAS # 115-07-1) is 8,600 µg/m3 based on an 8-hour averaging time.

#### Other adverse effects

no data available

### SECTION 13: Disposal considerations

#### **Disposal methods**

#### Product

The material can be disposed of by removal to a licensed chemical destruction plant or by controlled incineration with flue gas scrubbing. Do not contaminate water, foodstuffs, feed or seed by storage or disposal. Do not discharge to sewer systems.

#### Contaminated packaging

Containers can be triply rinsed (or equivalent) and offered for recycling or reconditioning. Alternatively, the packaging can be punctured to make it unusable for other purposes and then be disposed of in a sanitary landfill. Controlled incineration with flue gas scrubbing is possible for combustible packaging materials.

## **SECTION 14: Transport information**

#### **UN Number**

ADR/RID: UN1077 (For reference only, please check.) IMDG: UN1077 (For reference only, please check.) IATA: UN1077 (For reference only, please check.)

#### **UN Proper Shipping Name**

ADR/RID: PROPYLENE (For reference only, please check.) IMDG: PROPYLENE (For reference only, please check.) IATA: PROPYLENE (For reference only, please check.)

#### Transport hazard class(es)

ADR/RID: 2.1 (For reference only, please check.) IMDG: 2.1 (For reference only, please check.) IATA: 2.1 (For reference only, please check.)

#### Packing group, if applicable

ADR/RID: (For reference only, please check.) IMDG: (For reference only, please check.) IATA: (For reference only, please check.)

#### **Environmental hazards**

ADR/RID: No

IMDG: No

IATA: No

#### Special precautions for user

no data available

#### Transport in bulk according to IMO instruments

no data available

# **SECTION 15: Regulatory information**

#### Safety, health and environmental regulations specific for the product in question

European Inventory of Existing Commercial Chemical Substances (EINECS)

Listed.

#### **EC Inventory**

Listed.
United States Toxic Substances Control Act (TSCA) Inventory
Listed.
China Catalog of Hazardous chemicals 2015
Listed.
New Zealand Inventory of Chemicals (NZIoC)
Listed.
PICCS
Listed.
Vietnam National Chemical Inventory
Listed.
IECSC
Listed.
Korea Existing Chemicals List (KECL)
Listed.

# **SECTION 16: Other information**

#### Abbreviations and acronyms

CAS: Chemical Abstracts Service

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

RID: Regulation concerning the International Carriage of Dangerous Goods by Rail

IMDG: International Maritime Dangerous Goods

IATA: International Air Transportation Association

TWA: Time Weighted Average

STEL: Short term exposure limit

LC50: Lethal Concentration 50%

LD50: Lethal Dose 50%

EC50: Effective Concentration 50%

#### References

IPCS - The International Chemical Safety Cards (ICSC), website: http://www.ilo.org/dyn/icsc/showcard.home HSDB - Hazardous Substances Data Bank, website: https://toxnet.nlm.nih.gov/newtoxnet/hsdb.htm IARC - International Agency for Research on Cancer, website: http://www.iarc.fr/ eChemPortal - The Global Portal to Information on Chemical Substances by OECD, website: http://www.echemportal.org/echemportal/index? pageID=0&request\_locale=en CAMEO Chemicals, website: http://cameochemicals.noaa.gov/search/simple ChemIDplus, website: http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp ERG - Emergency Response Guidebook by U.S. Department of Transportation, website: http://www.phmsa.dot.gov/hazmat/library/erg Germany GESTIS-database on hazard substance, website: http://www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index-2.jsp ECHA - European Chemicals Agency, website: https://echa.europa.eu/

#### **Other Information**

High concentrations in the air cause a deficiency of oxygen with the risk of unconsciousness or death. Check oxygen content before entering

area.Turn leaking cylinder with the leak up to prevent escape of gas in liquid state.

**Disclaimer:** 

The information in this MSDS is only applicable to the specified product, unless otherwise specified, it is not applicable to the mixture of this product and other substances. This MSDS only provides information on the safety of the product for those who have received the appropriate professional training for the user of the product. Users of this MSDS must make independent judgments on the applicability of this SDS. The authors of this MSDS will not be held responsible for any harm caused by the use of this MSDS.