Chemical Safety Data Sheet MSDS / SDS

tert-Butanol

Revision Date: 2025-01-25 Revision Number: 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

 Product name
 : tert-Butanol

 CBnumber
 : CB5206388

 CAS
 : 75-65-0

 EINECS Number
 : 200-889-7

Synonyms : TBA,TERT-BUTANOL

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : For R&D use only. Not for medicinal, household or other use.

Uses advised against : none

Company Identification

Company : Chemicalbook

Address : Building 1, Huihuang International, Shangdi 10th Street, Haidian District, Beijing

Telephone : 400-158-6606

SECTION 2: Hazards identification

GHS Label elements, including precautionary statements

Symbol(GHS)



Signal word Danger

Precautionary statements

P501 Dispose of contents/container to.....

P405 Store locked up.

P403+P235 Store in a well-ventilated place. Keep cool.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P370+P378 In case of fire: Use ... for extinction.

P311 Call a POISON CENTER or doctor/physician.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continuerinsing.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P271 Use only outdoors or in a well-ventilated area.

P264 Wash skin thouroughly after handling.

P264 Wash hands thoroughly after handling.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P240 Ground/bond container and receiving equipment.

P233 Keep container tightly closed.

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

P202 Do not handle until all safety precautions have been read and understood.

P201 Obtain special instructions before use.

Hazard statements

H370 Causes damage to organs

H361 Suspected of damaging fertility or the unborn child

H336 May cause drowsiness or dizziness

H335 May cause respiratory irritation

H332 Harmful if inhaled

H331 Toxic if inhaled

H319 Causes serious eye irritation

H311 Toxic in contact with skin

H301 Toxic if swalloed

H225 Highly Flammable liquid and vapour

SECTION 3: Composition/information on ingredients

Substance

Product name : tert-Butanol

Synonyms : TBA,TERT-BUTANOL

CAS : 75-65-0

EC number : 200-889-7

MF : C4H10O

MW : 74.12

SECTION 4: First aid measures

Description of first aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Call in physician.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2) Foam Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

Special hazards arising from the substance or mixture

Carbon oxides

Flash back possible over considerable distance. Combustible.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapours possible in the event of fire. Forms explosive mixtures with air at ambient temperatures.


Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.

Further information

In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

NFPA 704



■ HEALTH 1 Exposure would cause irritation with only minor residual injury (e.g. <u>acetone</u>, sodium bromate, potassium chloride)

			Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature
	FIRE	3	conditions . Liquids having a flash point below 22.8 °C (73 °F) and having a boiling point at or above 37.8 °C (100 °F) or
			having a flash point between 22.8 and 37.8 °C (73 and 100 °F). (e.g. gasoline, acetone)
	REACT	0	Normally stable, even under fire exposure conditions, and is not reactive with water (e.g. helium, N2)
	SPEC.		
	HAZ.		
	•		

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition.

Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

Environmental precautions

Do not let product enter drains. Risk of explosion.

Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent material (e.g. Chemizorb?). Dispose of properly. Clean up affected area.

Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Change contaminated clothing. Preventive skin protection recommended. Wash hands after working with substance.

For precautions see section 2.2.

Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

control parameter

Hazard composition and occupational exposure limits

Does not contain substances with occupational exposure limits.

Exposure controls

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

Recommended Filter type: Filter A (acc. to DIN 3181) for vapours of organic compounds

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

Exposure limits

TLV-TWA 300 mg/m³ (100 ppm) (ACGIH); IDLH 8000 ppm.

SECTION 9: Physical and chemical properties

Information on basic physicochemical properties

Appearance	liquid
Odour	camphor-like
Odour Threshold	ca.71 ppm
pH	at 20 °C neutral
Melting point/freezing point	Melting point/range: 23 - 26 °C
Initial boiling point and boiling range	83 °C
Flash point	15 °C - closed cup
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Upper/lower flammability or explosive	Upper explosion limit: 8,0 %(V) Lower explosion limit: 2,3 %(V)
limits	
Vapour pressure	40,7 hPa at 20 °C

Vapour density	2,56
Relative density	No data available
Water solubility	at 20 °C soluble
Partition coefficient: n-octanol/water	log Pow: 0,30 - Bioaccumulation is not expected.
Autoignition temperature	470 °C at 1.013 hPa
Decomposition temperature	No data available
Viscosity	Viscosity, kinematic: No data available Viscosity, dynamic: 3,3 mPa.s at 30 °C
Explosive properties	No data available
Oxidizing properties	No data available
Henry's Law Constant	1.22 at 25 °C (static headspace-GC, Merk and Riederer, 1997)
λmax	λ: 215 nm Amax: 1.00
	λ: 230 nm Amax: 0.50
	λ: 250 nm Amax: 0.20
	λ: 300-350 nm Amax: 0.01

Other safety information

Dissociation constant 19,2 at 20 °C

Relative vapor density

2,56

SECTION 10: Stability and reactivity

Reactivity

Vapors may form explosive mixture with air.

Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

Possibility of hazardous reactions

Violent reactions possible with: Alkali metals

Alkaline earth metals Strong acids Aluminum

Strong oxidizing agents

Conditions to avoid

Warming.

Incompatible materials

rubber, various plastics

Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - male and female - 2.733 mg/kg (US-EPA)

Remarks: (Regulation (EC) No 1272/2008, Annex VI)

Acute toxicity estimate Inhalation - Expert judgment - 4 h - 11,1 mg/l Dermal

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation - 24 h (Draize Test)

Serious eye damage/eye irritation

Eyes - Rabbit (US-EPA)

Respiratory or skin sensitization

Sensitisation test (Magnusson and Kligman): - Guinea pig Result: negative

(OECD Test Guideline 406)

Germ cell mutagenicity

Test Type: In vitro mammalian cell gene mutation test Test system: Mouse lymphoma test

Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 476

Result: negative

Test Type: Micronucleus test Species: Mouse

Cell type: Red blood cells (erythrocytes) Application Route: Oral

Method: OECD Test Guideline 474 Result: negative

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

Inhalation - May cause respiratory irritation. - Respiratory system Inhalation - May cause drowsiness or dizziness. - Nervous system

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Toxicity

LD50 orally in rats: 3.5 g/kg (Schaffarzick, Brown)

SECTION 12: Ecological information

Toxicity

Toxicity to fish

flow-through test LC50 - Pimephales promelas (fathead minnow) - > 961 mg/l - 96 h

(OECD Test Guideline 203)

Toxicity to daphnia and other aquatic invertebrates

static test EC50 - Daphnia magna (Water flea) - 933 mg/l - 48 h (Directive 67/548/EEC, Annex V, C.2.)

Toxicity to algae

IC50 - Desmodesmus subspicatus (green algae) - > 1.000 mg/l - 72 h

Remarks: (IUCLID)

Toxicity to bacteria

EC10 - Pseudomonas putida - 6.900 mg/l - 16 h Remarks: (External MSDS)

Persistence and degradability

Biodegradability Result: > 99,9 % - Readily eliminated from water

(OECD Test Guideline 302B)

Bioaccumulative potential

No data available

Mobility in soil

No data available

Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Toxics Screening Level

The ITSL for t-butanol is 1890 μg/m3, with annual averaging time. The initial risk screening level (IRSL) for tert-butyl alcohol is 7 μg/m 3 (annual averaging time) and the secondary screening level (SRSL) is 70 μg/m 3 (annual averaging time).

Other adverse effects

Stability in water

Remarks: No data available

SECTION 13: Disposal considerations

Waste treatment methods

Product

See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

Incompatibilities

tert-Butanol is incompatible with strong acids (including mineral acid), including mineral acids; strong oxidizers or caustics, aliphatic amines; isocyanates, alkali metals (i.e., lithium, sodium, potassium, rubidium, cesium, francium).

Waste Disposal

Incineration, or bury absorbed waste in an approved land fill.

SECTION 14: Transport information

UN number

ADR/RID: 1120 IMDG: 1120

UN proper shipping name

ADR/RID: BUTANOLS IMDG: BUTANOLS IATA: Butanols

Transport hazard class(es)

ADR/RID: 3 IMDG: 3 IATA: 3

Packaging group

ADR/RID: II IMDG: II IATA: II

Environmental hazards

ADR/RID: no IMDG Marine pollutant: no IATA: no

Special precautions for user

No data available

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations on the Safety Management of Hazardous Chemicals

China Catalog of Hazardous chemicals 2015:Listed. website: https://www.mem.gov.cn/

Measures for Environmental Management of New Chemical Substances

Chinese Chemical Inventory of Existing Chemical Substances (China IECSC):Listed. website: https://www.mee.gov.cn/

EC Inventory:Listed.

European Inventory of Existing Commercial Chemical Substances (EINECS):Listed. website: https://echa.europa.eu/

Korea Existing Chemicals List (KECL):Listed. website: http://ncis.nier.go.kr

New Zealand Inventory of Chemicals (NZIoC):Listed. website: https://www.epa.govt.nz/

Philippines Inventory of Chemicals and Chemical Substances (PICCS):Listed. website: https://emb.gov.ph/

United States Toxic Substances Control Act (TSCA) Inventory:Listed. website: https://www.epa.gov/

Vietnam National Chemical Inventory:Listed. website: https://chemicaldata.gov.vn/

SECTION 16: Other information

Abbreviations and acronyms

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

CAS: Chemical Abstracts Service

EC50: Effective Concentration 50%

IATA: International Air Transportation Association

IMDG: International Maritime Dangerous Goods

LC50: Lethal Concentration 50%

LD50: Lethal Dose 50%

RID: Regulation concerning the International Carriage of Dangerous Goods by Rail

STEL: Short term exposure limit TWA: Time Weighted Average

References

[1] CAMEO Chemicals, website: http://cameochemicals.noaa.gov/search/simple

[2] ChemlDplus, website: http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp

[3] ECHA - European Chemicals Agency, website: https://echa.europa.eu/

[4] eChemPortal - The Global Portal to Information on Chemical Substances by OECD, website:

http://www.echemportal.org/echemportal/index?pageID=0&request locale=en

- [5] ERG Emergency Response Guidebook by U.S. Department of Transportation, website: http://www.phmsa.dot.gov/hazmat/library/erg
- [6] Germany GESTIS-database on hazard substance, website: http://www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index-2.jsp
- [7] HSDB Hazardous Substances Data Bank, website: https://toxnet.nlm.nih.gov/newtoxnet/hsdb.htm
- [8] IARC International Agency for Research on Cancer, website: http://www.iarc.fr/
- [9] IPCS The International Chemical Safety Cards (ICSC), website: http://www.ilo.org/dyn/icsc/showcard.home
- 【10】Sigma-Aldrich, website: https://www.sigmaaldrich.com/

Other Information

The odour warning when the exposure limit value is exceeded is insufficient.

Disclaimer:

The information in this MSDS is only applicable to the specified product, unless otherwise specified, it is not applicable to the mixture of this product and other substances. This MSDS only provides information on the safety of the product for those who have received the appropriate professional training for the user of the product. Users of this MSDS must make independent judgments on the applicability of this SDS. The authors of this MSDS will not be held responsible for any harm caused by the use of this MSDS.